

item #	
model #	
project #	
sis#	
aia #	



# RETHERM RRS071C

Regeneration oven to reheat refrigerated (+3°C) and frozen food (-18°C)

## CONSTRUCTION FEATURES

- Tightness chamber with radiused corners
- Total thermic insulation with rock or glass wool
- Long lasting front seal, made up of food-grade and high-heat resistant silicone, easy to clean and extremely resistant
- Removable side racks to facilitate cleaning
- Ventilated heating provided by high efficiency protected heating elements
- Snap-shut door
- Adjustable feet
- Easy access to facilitate maintenance and repair

### FUNCTIONAL FEATURES

- Control panel of temperature electromechanical
- Simplified, user-friendly controls
- Operating temperature 30°C 160°C
- Humidity vent
- Periodic reversal of direction of rotation of the fan for better air distribution
- Automatic stopping of fans when is opened
- End-of-cycle buzzer
- Chamber with safety thermostat

### STANDARD SUPPLY

• Removable GN 1/1 tray racks

# OPTIONS & ACCESSORIES

Support
Grids
Trays

#### MODULINESRL



### TECHNICAL INSTALLATION DIAGRAM


Overall dimensions


Electricity supply cable inlet



Vent for excess humidity







825 x 680 x 725h (W x D x H) - mm Trays capacity 7 GN 1/1 14 ø 200-260 Plates capacity 7 ø 270-320 380-415V 3N 50/60Hz Power supply **Total input** В 6,3 (400V) [kW] Amps. 9,2 (400V) [A] Operating 30 ÷ 160 temperature [°C] Product max 25 capacity [Kg] Distance 75 [mm] moduline Net weight 54 [Kg]

#### With electromechanical control

- A On/Off switch
- B Regenerating time setting knob, with warming light indicating operation
- C Temperature regulation knob, with warning light to show that temperature has been reached

#### MODULINESRL