



REThERM GRE106EW

Regeneration oven
to reheat refrigerated
food (+3°C)

CONSTRUCTION FEATURES

- Tightness chamber with radiused corners
- Total thermic insulation with rock or glass wool
- Long lasting front seals made up of food grade of high heat resistance
- Internal drain for easy cleaning
- Ventilated heating provided by high efficiency protected heating elements
- Snap-shut door
- Adjustable feet
- Easy access to facilitate maintenance and repair
- Condensation drip tray under the door and connected to the oven drainage system.

FUNCTIONAL FEATURES

- Electronic control panel with LCD 4,3" touch-screen display
- Simplified, user-friendly controls
- Periodic reversal of direction of rotation of the fan for better air distribution
- Automatic stopping of fans when the door is opened
- End-of-cycle buzzer
- Chamber with safety thermostat
- Operating temperature 30°C ÷ 210°C
- The regeneration program can be divided into different phases
- Self-diagnosis system
- MultiLevel function: Combi is able to manage different dishes with different cooking times or temperatures
- IdealWarm function: the intelligent temperature decrease in the cavity at the end of the cooking cycle allows perfect warm holding
- Climachef system
- PadLock: key lock system with password
- ProTime system allows you to set the date and the time you want the oven to preheat or start working
- Removable GN1/1 tray racks
- EcoWash self-cleaning system

OPTIONS & ACCESSORIES

- | | | |
|--|---|--|
| <input type="checkbox"/> Supports | <input type="checkbox"/> Stacking kit | <input type="checkbox"/> Grids |
| <input type="checkbox"/> Single-point core probe | <input type="checkbox"/> Usb port | <input type="checkbox"/> Trays |
| <input type="checkbox"/> Multipoint core probe | <input type="checkbox"/> SpeedGrade fan speed adjustment | <input type="checkbox"/> Sound silencer |
| <input type="checkbox"/> Needle core probe, thin | <input type="checkbox"/> Water filter system | <input type="checkbox"/> Air condensation hood |
| <input type="checkbox"/> External hand shower | <input type="checkbox"/> Double low-emission glass door with internal ventilation | <input type="checkbox"/> One Touch Software |
| <input type="checkbox"/> Integral quenching system | Openable inside glass of the door | <input type="checkbox"/> Opposite side opening |
| <input type="checkbox"/> Double-click door opening | | <input type="checkbox"/> Door lock with key (in combination with glass door) |

MODULINESRL

